

SYSTEM NOTES:

- 1. FRAME & PANEL CONSTRUCTION: HEAVY DUTY EXTRUDED ALUMINUM SUB FRAME AND SCREEN FRAME.
- 2. FRAME CONTAINS FULL LENGTH PIANO HINGE ALONG THE TOP OF THE SECURITY SCREEN.
- 3. FABRIC CONSTRUCTION: SCREEN FABRIC IS MADE UP OF T-304 STAINLESS STEEL, WITH .028" WIRE ARRANGED 12 STRANDS PER INCH.
- 4. THE SCREEN FABRIC IS ATTACHED TO THE EXTRUDED ALUMINUM PANEL FRAME WITH THE SCREEN RETAINER SYSTEM.
- 5. ALUMINUM EXTRUDED FRAME AND WIRE MESH ARE POWDER COATED WITH A STANDARD COLORS.

Optional sub frames can be used with our narrow site or heavy duty security screen frames.

		CUST. NAME		1.	PART NUMBER:	VARIO	DUS	
	TOLERANCES EXCEPT AS NOTED	PART NAME: NA	NARROW SITE WITH SUB FRAME		MATERIAL	AL: ALUMINUM WITH STAINLESS STEEL		
	reference	TREATMENT:	POWDER COATED		SHEET #	#1 OF1 SHEETS		
		W. W				DRAWN BY:	CHECKED BY:	
	,X ± ,060		CENTURION SECURITY SCREEN COMPANY, LTD.			GMP	DATE: 1-12-2010	
	.XX ± .030	The state of the s						
	.XXX ± .015							
	ANGULAR ± 1°	This information is considered proprietary to Centurion Security Screen Co, LTD, and shall not be given to a third party without express permission			THIRD ANGLE PROJECTION			
				•• u	SCALE: NTS			

UNLESS OTHERWISE NOTED, DIMENSIONS ARE IN INCHES